


Demoverision mit Originalinhalten



GENERAL INFORMATION

SPECIFICATIONS

ITEM			
DIMENSIONS	Overall length	2,155 mm (84.8 in)	
	Overall width	780 mm (30.7 in)	
	Overall height	1,195 mm (47.0 in)	
	Wheelbase	1,485 mm (58.5 in)	
	Seat height	795 mm (31.3 in)	
	Ground clearance	145 mm (5.7 in)	
	Dry weight	213 kg (469.6 lb), California type: 214 kg (471.8 lb)	
FRAME	Type	Double cradle	
	Front suspension	Telescopic fork	
	Rear suspension	Swing arm/shock absorber	
	Front tire size	110/90-16 59H	
	Rear tire size	130/90-16 67H	
	Cold tire pressures	Driver only	Front 225 kPa (2.25 kg/cm ² , 32 psi) Rear 225 kPa (2.25 kg/cm ² , 32 psi)
		Driver and passenger	Front 225 kPa (2.25 kg/cm ² , 32 psi) Rear 280 kPa (2.80 kg/cm ² , 40 psi)
	Front brake, lining swept area	Disc brake, 904 cm ² (140 sq in)	
	Rear brake, lining swept area	Drum brake, 198 cm ² (31 sq in)	
	Fuel capacity	16 liters (4.2 US gal, 3.52 Imp gal)	
Fuel reserve capacity	2.5 liters (2.6 US qt, 2.2 Imp qt)		
Caster angle	60°		
Trail	122 mm (4.8 in)		
Front fork oil capacity	Right 423 cc (14.3 ozs) Left 429 cc (14.5 ozs)		
ENGINE	Type	Air cooled 4-stroke, DOHC	
	Cylinder arrangement	Vertical in line four	
	Bore and stroke	67.0 x 49.4 mm (2.64 x 1.94 in)	
	Displacement	696 cm ³ (42.6 cu in)	
	Compression ratio	9.3 : 1	
	Valve train	Chain driven DOHC, 4 valves per cylinder	
	Maximum horsepower	80 PS/10,000 rpm	
	Maximum torque	6.25 kg-m (45.20 lb-ft)/8,000 rpm	
	Oil capacity	'84- 3.6 liters (3.8 US qt, 3.2 Imp qt) after disassembly After '84- 4.1 liters (4.3 US qt, 3.6 Imp qt) after disassembly	
	Lubrication system	Wet sump	
	Air filtration	Paper	
	Cylinder compression	1200 ± 200 kPa (12.0 ± 2.0 kg/cm ² , 175 ± 30 psi)	
	Valve clearance	10° (BTDC) at 1 mm lift, 42° (BTDC) at 0 lift 40° (ABDC) at 1 mm lift, 80° (ABDC) at 0 lift	

mopedreifen.de

#Bestellservice

Die originalen Unterlagen bekommen Sie beim Kauf von uns automatisch in der Bestellmail zugesandt.

#Stammkunden

Für eingeloggte Stammkunden stehen die originalen Freigaben auch weiterhin zum downloaden bereit.